



## AURIGINØ SUMMARY PAGE

(11) Publication number: 02645942 B2

(45) Publication Date: 25.08.97

Application Publication No.: 05108415 A2

(43) Date of publication of application: 27.04.93

(51) Int. Cl. 6F01L 13/00 6F01L 9/02 6F02D 13/02

(21) Application number: 03297621

(22) Date of filing: 18.10.91

(30) Priority: 18.10.91 JP 297621

(71) Applicant: HINO MOTORS LTD

(72) Inventor: KAKEGAWA TOSHIKI

(54) INTAKE AND EXHAUST VALVE CONTROL  
METHOD OF INTERNAL COMBUSTION ENGINE  
AND DEVICE THEREOF

## (57) Abstract:

**PURPOSE:** To reduce energy loss, and control a lift limiting and a lift amount freely, while simplifying a system, in a device in which the intake and exhaust valves of an internal combustion engine are opened/closed by oil pressure.

**CONSTITUTION:** A free piston 8 is pushed by high oil pressure switched by means of a solenoid valve 13 through a constant stroke smaller than the whole valve lift amount, and a plunger 9 which abuts on the free piston 8 and a valve stem 1 is struck by the free piston 8. The valve stem 1 is pushed by the inertia of the plunger 9 after the constant stroke end of the free piston 8 opposing to a valve spring 2, and the plunger 9 is pushed by low oil pressure switched by means of a solenoid valve 17 so as to stop a valve to a prescribed position.

COPYRIGHT: (C)1993,JPO&amp;Japio

